



NORTH



AMERICAN

WWW.NAAUTOEQUIPMENT.COM

866-607-4022

7,000 lb./ 9,000 lb. capacity and large 3" cylinder, one-piece diamond-plate runways and scratch-resistant powder coat paint.


FP7K
Storage/ Service lift



Features:

- ◆ 7,000 lb./9,000 lb. lifting capacity
- ◆ Carriages completely enclosed for safety
- ◆ Aircraft quality cables rated at 14,500 lbs.
- ◆ 18 1/2" wide runways formed with one piece 3/16" non-skid diamond plate
- ◆ Hydraulic pump available in 110 or 220vac
- ◆ Easy operation—lock handle is located by power unit minimizing any bending or squatting
- ◆ Large 3" diameter cylinder is located safely under runway

-Options




Solid Deck Option

Large storage area. Two diamond plate platforms drop between tracks for storage of snowmobiles, ATVs and garden equipment. Constructed of lightweight aluminum.



One-Step Caster Kit

Easy to install with no tools— simply pin them on, lower lift, casters automatically lift the columns; allows mobility with or without a vehicle; turn lift sideways to park two vehicles underneath.



Aluminum Approach Ramps

These lightweight ramps weigh only 18 lbs. each compared with the 53 lbs. of standard ramps.



Stackable Poly Drip Trays, 3

Lightweight polyethylene; stackable; simply slide to back and stack! 8" or 12" widths.

SPECIFICATIONS	FP9K (Not Shown)	FP7K	FP7K-XLT (Not Shown)
Lifting capacity	9,000 lbs.	7,000 lbs.	7,000 lbs.
Overall length (to outside base plates)	175"	171"	190"
Total width (to outside base plates)	105 3/8"	112"	112"
Overall height	82"	84"	92"
Track length (without ramp)	165"	160"	180 3/4"
Track width	18 1/2"	18 1/2"	18 1/2"
Rate of lift	90 sec.	90 sec.	100 sec.
Width between posts	94"	99"	100"
Maximum clearance under tracks	73"	65"	78"
Shipping weight	1,485 lbs.	1,485 lbs.	1,680 lbs.

sales@naautoequipment.com